

## Programmable Display and Controller

### Programmable Display and Controller

Extremely versatile device designed to provide intuitive user interaction and realtime control in diverse applications. With its sleek design and fully customizable user interface, it offers seamless integration into different environments and systems. It offers a blend of flexibility, functionality, and aesthetics, making it a valuable addition to diverse environments. Whether for residential, commercial, or industrial use, its customizable interface, multi-protocol communication capabilities, and easy-to-clean, bezel-less glass front ensure seamless integration, efficient operation, and user safety.



The aesthetic design prioritizes user safety and hygiene with a seamless edge-to-edge bezel-free glass front making it easy to clean and disinfect. The two-piece construction allows the base to be mounted on the wall for wiring and preparation, while the display part can be easily snapped on later when the site is ready. This modular design simplifies installation and minimizes the risk of damage during construction.

The user interface can be easily customized to suit individual requirements, providing a tailored user experience. Elements, such as buttons, menus, and widgets, can be freely added and arranged through a user-friendly graphical programming tool. The device supports different graphical widgets, giving users the option to choose the layout and design that aligns with their aesthetic preferences and usability preferences.

The device is equipped with multiple communication ports supporting various industry standard protocols simultaneously, including BACnet, Modbus, Dali and KNX, and more - enabling seamless integration of a wide range of systems and devices. Built-in sensors for measuring temperature and relative humidity are present across all versions. Additionally, an optional feature for CO2 measurement is available. This capability enables users to effectively monitor indoor air quality and activate automated routines to ensure a comfortable and healthy environment.

This device not only serves as a user interface but also possesses the capability to execute programmed control logic in real-time locally and independently, with no reliance on a higher system. This empowers system integrators to create and implement custom control strategies locally increasing system reliability.

The device offers exceptional versatility by providing control over HVAC systems, lighting, blinds, and more. Its capability to manage a wide range of functions makes it a unique tool for creating a comfortable and efficient environment in office buildings, hospitality, health care institutions, shopping centers, homes and extending to industrial applications.

Sedona Open Control provides a complete software platform for developing, deploying, integrating, and managing pervasive device applications at the lowest level. It brings the power of programmable control and the Internet down to extremely inexpensive devices. Sedona distributes decision making control and manageability to any device and brings intelligence and connectivity to the network edge and back.

- 4.3" capacitive color touch-screen
- Edge to edge glass facia
- Fully customizable graphics
- Freely programmable
- Powered by Sedona Open Control
- Multiple communication ports
- Integrated temperature and humidity sensor, CO2 option (in development)
- Belimo MP-Bus option
- Dali (Digital Addressable Lighting Interface) option
- Real-time control

## Specifications

---

|   |  |
|---|--|
| <b>Operating voltage</b>                                | 24 VAC/DC $\pm 10\%$   |
| <b>Power consumption (Max)</b>                          | 4 VA   |
| <b>Mounting</b>   | Flush wall mount using <ul style="list-style-type: none"><li>- standard European round electrical wall box, Ø60 mm, min. 45mm depth</li><li>- standard UK style wall box 86x86 mm</li><li>- standard CH style wall box</li></ul> |
| <b>Display</b>  | 4.3" Capacitive touch-screen<br>800 x 480 pixel resolution<br>65K colors   |
| <b>On-board Temperature Sensor Accuracy (at sensor)</b> | $\pm 0.2K$ @ 25°C  |
| <b>On-board Humidity Sensor Accuracy (at sensor)</b>    | $\pm 3\%$ RH between 20-80% RH   |
| <b>Operating Temperature</b>                            | +5 to +50 °C   |
| <b>Storage Temperature</b>                              | -25 to +75 °C  |
| <b>Relative Humidity</b>                                | 5 - 95%, non-condensing  |
| <b>Weight</b>   | 215 grams (280 grams with packaging)   |
| <b>Package dimensions</b>                               | 135 x 100 x 97 mm (LxWxH)  |
| <b>Protection</b>                                       | IP30 according to EN 60529   |
| <b>Terminal Size</b>                                    | For power up to 1.5 mm <sup>2</sup> / 16 AWG<br>For comms up to 1 mm <sup>2</sup> / 17 AWG   |
| <b>Communication Ports (depending on version)</b>       | Port 1: Main RS485 (BACnet Slave, Modbus RTU master or slave)<br><br>Port 2 : Auxiliary RS485 (Modbus RTU master)<br>Port 3: DALI (Master) or Belimo MP-Bus (Master)   |
| <b>Programming Port</b>                                 | Standard USB-C type  |

## Worldwide Locations

---

### United States

Contemporary Control Systems, Inc.

Tel: +1 630 963 7070  
Fax: +1 630 963 0109

[info@ccontrols.com](mailto:info@ccontrols.com)

### Germany

Contemporary Controls GmbH

Tel: +49 341 520359 0  
Fax: +49 341 520359 16

[ccg.info@ccontrols.com](mailto:ccg.info@ccontrols.com)

### United Kingdom

Contemporary Controls Ltd

Tel: +44 (0)24 7641 3786  
Fax: +44 (0)24 7641 3923

[ccl.info@ccontrols.com](mailto:ccl.info@ccontrols.com)

### China

Contemporary Controls (Suzhou) Co. Ltd

Tel: +86 512 68095866  
Fax: +86 512 68093760

[info@ccontrols.com.cn](mailto:info@ccontrols.com.cn)